

30 May 2024

Chris Schneider Managing Director National Ceramic Industries Australia PO Box 765 Maitland NSW 2320

Dear Chris,

Environmental Monitoring for National Ceramic Industries Australia - April 2024

Please find enclosed the documentation for the environmental monitoring carried out for National Ceramic Industries Australia during April 2024. Sampling methodology and adopted assessment criteria are detailed below.

1.0 Sampling Methodology

Sampling was performed by AECOM Australia Pty Ltd (AECOM) and sample analysis was carried out by ALS NATA accredited laboratory. All sampling and analysis were carried out in accordance with Environmental Protection Authority (EPA) approved methods with reference to the following Australian Standards:

- monitoring of fine suspended particulates (PM₁₀) on the EPA six-day cycle in accordance with:
 - AS/NZS 3580.9.6 (2015) Methods for the Sampling and Analysis of Ambient Air Determination of Suspended Particulate Matter – PM₁₀ High Volume Sampler with Size Selective Inlet – Gravimetric Method.
- monitoring of fluorides in ambient air in accordance with:
 - AS/NZS 3580.13.2 (2013) Determination of fluorides Gaseous and acid-soluble particulate fluorides Manual, double filter paper sampling.
- meteorological monitoring in accordance with:
 - AS 3580.1.1 (2016) Methods for sampling and analysis of ambient air Part 1.1 Guide to siting air monitoring equipment.
 - AS 3580.14 (2014) Methods for sampling and analysis of ambient air Part 14: Meteorological monitoring for ambient air quality monitoring.
- monitoring of surface water quality in accordance with:
 - AS/NZS 5667.1:1998 (R2016) Guidance on the design of sampling programs, sampling techniques and the preservation and handling of samples.
 - AS/NZS 5667.4:1998 (R2016) Guidance on sampling from lakes, natural and manmade.

2.0 Assessment Criteria

Suspended particulate loads are assessed against the impact assessment criteria defined in the Project Approval conditions (09_0006 – National Ceramic Industries Australia Tile Manufacturing Facility Expansion Project, 19 January 2012). The assessment criteria for PM_{10} (particulate matter with an aerodynamic diameter of less than 10 μ m) are:

- 50 μg/m³ over a 24-hour period
- 30 μ g/m³ as an annual average.

Ambient fluoride concentrations are assessed against the guidelines defined in NSW EPA Approved Methods for the Modelling and Assessment of Air Pollutants in New South Wales (NSW EPA (2022)).



The NSW EPA impact assessment criteria for ambient fluoride are:

- 2.9 µg/m³ over a 24-hour period
- 1.7 μg/m³ over a 7-day period.

Surface waters are assessed in accordance with default trigger values for physical and chemical stressors for southeast Australia in the *Australian and New Zealand Guidelines for Fresh and Marine Water Quality* (ANZG, 2018). These values are:

- pH in the range of 6.5 8.5 (Table 3.3.2 NSW Lowland River)
- electrical conductivity (EC) in the range of 125 2200 µS/cm (Table 3.3.3 NSW Lowland River).

3.0 Monitoring Results

Monitoring results for the month of April 2024 are presented in the attachments to this letter. Monitoring results for the preceding two months are also presented to demonstrate quarterly trends in results.

The April 2024 monitoring results show that all ambient PM_{10} results were below the short-term impact assessment criterion (50 µg/m³) as defined in the DPIE Project Approval (Schedule 3, Condition 15, Table 2).

The PM₁₀ rolling annual average concentration at the Southeast site remains below the Project Approval annual criterion of 30 μ g/m³ with an average of 15.9 μ g/m³ following the April monitoring period. The Northwest annual average is also below the criteria and is sitting at 21.5 μ g/m³ following the completion of the April monitoring period.

Fluoride results for April remain below the relevant assessment criteria at both the Northwest and Southeast monitoring sites with no exceedances of either the 24 hour ($2.9 \ \mu g/m^3$) or 7-day ($1.7 \ \mu g/m^3$) criteria this month. Catch up samples were performed on 1 May at both the North West and South East locations for recent 24hr fluoride samples that were not analysed (detailed in the March report).

Pond 4, being the last detention pond on site before water potentially leaves the site is monitored for pH, Electrical Conductivity and Temperature on a weekly basis. The adopted ANZG 2018 guidelines for pH and conductivity are the default trigger values for slightly disturbed aquatic ecosystems in NSW lowland rivers.

pH measurements for April 2024 were within both the upper and lower limits of the adopted guidelines with no water was observed to be flowing offsite during the month.

All electrical conductivity measurements for April were within both upper and lower limits of the adopted guidelines. Water temperature was also measured weekly however no guideline is available for assessment. Pond 4 was not observed to be flowing offsite throughout April 2024.

A figure showing the monitoring locations and monitoring results and plots can be found attached along with the wind rose for April. Laboratory certificates, field sheets and calibration data along with relevant meteorology data can be provided on request.

If you require any further information, please contact Cye Buckland on 0488 777 160.

Yours faithfully,

cye.buckland@aecom.com Mobile: +61 488 777 160

encl: Monitoring data tables and charts, wind rose, monitoring locations

North West Monitoring Location - 24 hour PM10 Monitoring

	North West - 24 hour PM10 Monitoring						
February 2024 to April 2024							
Monitoring Event	24-hr PM ₁₀	24-hr PM ₁₀ Criterion	PM ₁₀ Annual Average	PM ₁₀ Annual Average Criterion			
	(µg/m3)	(µg/m³)	(µg/m³)				
5-Feb-24	48.0	50	21.2	30			
11-Feb-24	20.4	50	21.2	30			
17-Feb-24	19.1	50	21.3	30			
23-Feb-24	34.5	50	21.7	30			
29-Feb-24	29.4	50	21.9	30			
6-Mar-24	22.7	50	21.6	30			
12-Mar-24	27.4	50	21.7	30			
18-Mar-24	9.9	50	21.6	30			
24-Mar-24	12.5	50	21.5	30			
30-Mar-24	11.1	50	21.5	30			
5-Apr-24	5.7	50	21.3	30			
11-Apr-24	16.2	50	21.3	30			
17-Apr-24	20.3	50	21.3	30			
23-Apr-24	13.8	50	21.3	30			
29-Apr-24	29.6	50	21.5	30			



North West - 7 Day Fluoride Monitoring						
March 2024 to May 2024						
Monitoring Event Particulate Fluoride Gaseous Fluoride Criterion						
Start Date	End Date	(μg/m ³ as HF at STP)	(μg/m ³ as HF at STP)	(µg/m ³ as HF at STP)	(μg/m ³ as HF at STP)	
8-Feb-24	15-Feb-24	0.071	0.400	0.471	1.7	
15-Feb-24	22-Feb-24	0.038	0.254	0.292	1.7	
22-Feb-24	28-Feb-24	0.032	0.383	0.415	1.7	
28-Feb-24	7-Mar-24	0.039	0.237	0.276	1.7	
7-Mar-24	14-Mar-24				1.7	
14-Mar-24	21-Mar-24	0.060	0.447	0.507	1.7	
21-Mar-24	28-Mar-24	0.032	0.145	0.177	1.7	
28-Mar-24	4-Apr-24	0.027	0.178	0.205	1.7	
4-Apr-24	12-Apr-24	0.063	0.157	0.220	1.7	
12-Apr-24	18-Apr-24	0.017	0.082	0.099	1.7	
18-Apr-24	26-Apr-24	0.002	0.015	0.017	1.7	
26-Apr-24	2-May-24	0.044	0.219	0.263	1.7	





Note: 7 March sample failed to run

North West Monitoring Location - 24 hour Fluoride Monitoring

North West - 24 hour Fluoride Monitoring					
February 2024 to April 2024					
Monitoring Event	24-hr Particulate Fluoride	24-hr Gaseous Fluoride	24-hr Total Fluoride	24-hr Total Fluoride Guideline Criterion	
	(μg/m ³ as HF at STP)				
05-Feb-24	0.018	0.243	0.261	2.9	
11-Feb-24	0.015	0.272	0.287	2.9	
17-Feb-24	0.016	0.279	0.295	2.9	
23-Feb-24	0.017	0.173	0.190	2.9	
29-Feb-24	0.033	0.284	0.317	2.9	
06-Mar-24	0.016	0.080	0.096	2.9	
12-Mar-24	0.016	0.164	0.180	2.9	
18-Mar-24	0.016	0.204	0.220	2.9	
24-Mar-24	0.015	0.174	0.189	2.9	
30-Mar-24				2.9	
05-Apr-24	0.012	0.110	0.122	2.9	
11-Apr-24	0.015	0.076	0.091	2.9	
17-Apr-24	0.029	0.086	0.115	2.9	
23-Apr-24	0.230	1.578	1.808	2.9	
29-Apr-24	0.029	0.065	0.094	2.9	
01-May-24	0.145	0.600	0.745	2.9	



Note - 30 March sample did not run. Catch up sample performed 1 May.

South East Monitoring Location - 24 hour PM10 Monitoring



	South East - 7 Day Fluoride Monitoring					
	February 2024 to May 2024					
Monitoring Event Particulate Fluoride Fluoride Fluoride Fluoride Criterion						
Start Date	End Date	(μg/m ³ as HF at STP)				
8-Feb-24	15-Feb-24	0.005	0.086	0.091	1.7	
15-Feb-24	22-Feb-24	0.013	0.140	0.153	1.7	
22-Feb-24	28-Feb-24	0.007	0.121	0.128	1.7	
28-Feb-24	7-Mar-24	0.016	0.213	0.229	1.7	
7-Mar-24	14-Mar-24	0.020	0.113	0.133	1.7	
14-Mar-24	21-Mar-24	0.008	0.164	0.172	1.7	
21-Mar-24	28-Mar-24	0.012	0.257	0.269	1.7	
28-Mar-24	4-Apr-24	0.011	0.300	0.311	1.7	
4-Apr-24	12-Apr-24	0.018	0.214	0.232	1.7	
12-Apr-24	18-Apr-24	0.008	0.203	0.211	1.7	
18-Apr-24	26-Apr-24	0.007	0.193	0.200	1.7	
26-Apr-24	2-May-24	0.006	0.065	0.071	1.7	



South East Monitoring Location - 7 Day Fluoride Monitoring

South East - 24 hour Fluoride Monitoring					
February 2024 to April 2024					
Monitoring Event	24-hr Particulate Fluoride	24-hr Gaseous Fluoride	24-hr Total Fluoride	24-hr Total Fluoride Guideline Criterion	
	(μg/m ³ as HF at STP)				
5-Feb-24	0.033	0.231	0.264	2.9	
11-Feb-24	0.312	0.461	0.773	2.9	
17-Feb-24	0.015	0.204	0.219	2.9	
23-Feb-24	0.062	0.181	0.243	2.9	
29-Feb-24	0.032	0.162	0.194	2.9	
6-Mar-24	0.014	0.126	0.140	2.9	
12-Mar-24	0.014	0.264	0.278	2.9	
18-Mar-24	0.015	0.125	0.140	2.9	
24-Mar-24				2.9	
30-Mar-24	0.014	0.295	0.309	2.9	
5-Apr-24	0.084	1.506	1.590	2.9	
11-Apr-24	0.014	0.119	0.133	2.9	
17-Apr-24	0.013	0.096	0.109	2.9	
23-Apr-24	0.013	0.465	0.478	2.9	
29-Apr-24	0.024	0.193	0.217	2.9	
1-May-24	0.012	0.516	0.528	2.9	
24 March sample not analysed due to sampling time being					

significantly more than 24hrs due to timer issue.



	Pond 4 - Weekly pH Monitoring				
	February 2024 to April 2024				
Monitoring Event	рН	ANZG pH trigger value - lower bound	ANZG pH trigger value - upper bound	Unable to sample	
	рН	pH	рН		
08-Feb-24	7.89	6.5	8.5		
15-Feb-24	8.96	6.5	8.5		
22-Feb-24	7.84	6.5	8.5		
28-Feb-24	8.98	6.5	8.5		
04-Mar-24	7.94	6.5	8.5		
07-Mar-24	8.54	6.5	8.5		
14-Mar-24	8.01	6.5	8.5		
21-Mar-24	7.64	6.5	8.5		
28-Mar-24	7.19	6.5	8.5		
08-Apr-24	7.26	6.5	8.5		
12-Apr-24	7.09	6.5	8.5		
18-Apr-24	7.85	6.5	8.5		
26-Apr-24	7.94	6.5	8.5		



	Pond 4 - Weekly EC Monitoring					
	February 2024 to April 2024					
Monitoring Event	EC	ANZG EC trigger value - lower bound	ANZG EC trigger value - upper bound	Unable to sample		
	µS/cm	μS/cm	μS/cm			
08-Feb-24	261	125	2200			
15-Feb-24	275	125	2200			
22-Feb-24	282	125	2200			
28-Feb-24	378	125	2200			
04-Mar-24	129	125	2200			
07-Mar-24	262	125	2200			
14-Mar-24	291	125	2200			
21-Mar-24	246	125	2200			
28-Mar-24	281	125	2200			
08-Apr-24	152	125	2200			
12-Apr-24	219	125	2200			
18-Apr-24	238	125	2200			
26-Apr-24	220	125	2200			



Pond 4 - Weekly Temperature Monitor	oring
February 2024 to April 2024	

Monitoring Event	Temperature	Unable to sample
	°C	
08-Feb-24	27.7	
15-Feb-24	24.9	
22-Feb-24	23.5	
28-Feb-24	30.2	
04-Mar-24	24.1	
07-Mar-24	26.7	
14-Mar-24	27.3	
21-Mar-24	24.5	
28-Mar-24	21.2	
08-Apr-24	20.6	
12-Apr-24	24.2	
18-Apr-24	22.4	
26-Apr-24	20.3	
	I	





- Ambient Air Monitoring Station
- NCIA Site Boundary
- Watercourse

AECOM

